

NewTom VGi evo

EXPANDED.VISION

EVOLVED 3D IMAGING



Cone Beam 3D Imaging
NewTom
what's next



VGi evo EXPANDED.VISION

FROM NEWTOM'S RESEARCH AND INNOVATION, THE COMPLETE MAXILLOFACIAL/ENT CBCT.

Detailed viewing accuracy, superior scanning technology. Multiple FOVs up to 24 x 19 cm for complete Head&Neck 3D diagnostics and 2D examinations in a single scan. The CineX function offers a dynamic view of moving structures. The dose radiated to the patient can be considerably reduced with the ECO Scan mode.

SUPERIOR VISION AND CLEAR DETAILS.

Extraordinary
performance and very
high quality 2D
and 3D images for
perfect diagnoses.

NewTom's research and experience has produced VGi evo, the versatile and efficient device that offers technology, safety, comfort and a broad range of FOVs for acquisitions up to 24 x 19 cm. A wide range of volumetric, panoramic and teleradiographic examinations as well as dynamic X-rays for perfect diagnoses in all situations.

With the exclusive Eco Scan acquisition modes and SafeBeam™ technology, excellent image quality can be ensured with very low radiated doses to safeguard the patient's health. The latest-generation head support unit and the technologically advanced control panel offer a simple and efficient user experience with comfortable patient positioning and guided workflow.



BROAD-RANGING DIAGNOSIS

High resolution images in a single scan of the whole **Head&Neck** area, from the cervical to the maxillofacial region, including ears and complete upper airways.



COMFORT AND PERFORMANCE

Easy and comfortable patient positioning with the patented head support unit for excellent image quality.



ECO DOSE

The result of NewTom's twenty-year long experience, ECO Scan mode allows quality diagnoses with low dose of radiations to safeguard the patient's health.



MAXIMUM VERSATILITY

A unique device for excellent volumetric, panoramic and teleradiographic investigations as well as 2D X-ray sequences.



THE NEW REFERENCE OF CBCT.

Outstanding
definition and quality
with the revolutionary
NewTom image chain.

The technologically advanced elements that form the innovative image chain of VGi evo carry the performance of CBCT devices to a new extraordinary level:

- the ultimate large sensor allows to examine a volume up to 24 x 19 cm with increased signal-noise ratio;
- the generator with rotating anode and 0.3 mm focal spot allows to obtain very high definition images to see details and microstructures that cannot be investigated with standard technological devices;
- reconstruction algorithms and image processing, the result of NewTom's twenty years of experience, allow to rapidly obtain exceptional 2D and 3D images.



360°

Complete 360° rotation to rapidly acquire superior quality cylindrical volume with advanced kinematic technology (patented).



HiRes

The degree of accuracy of NewTom Cone Beam CT technology is crucial in case of investigations for endodontics, periodontics and otorhinolaryngology, which require high resolution.




CBCT

The generator with rotating anode and small 0.3 mm focal spot, and SafeBeam™ technology that automatically adapts CBCT exposure parameters to suit the anatomical region investigated provide very high quality images.


EFFECTIVE PATIENT SUPPORT

The patented head support unit offers 7 stability (contact) points and laser guides for the utmost precision in the positioning of the patient. User-friendly and efficient, it is entirely free of metal to avoid artifacts. Its motor-driven chin rest allows to align the position of the field of view to the anatomical area of interest via a servo-assisted movement, also from the image acquisition workstation.



MULTIVISION (4 IN 1)

A single CBCT scan with the Sharp 2D (patented) function can automatically generate a series of 2D projections that include panoramic images and a sequence of teleradiographic images (AP, PA and LL).



aMAR (autoAdaptive Metal Artifact Reduction)

The aMAR algorithm generates an additional set of images that clearly shows the anatomical structures even when there are multiple metal objects, such as amalgam or implants, that would impair image quality.

EXTENDED 3D DIAGNOSTICS.

Complete FOV range
for perfect
3D volumes
in all situations.

VGi evo is a versatile and effective device with several examination modes dedicated to an extensive selection of clinical applications. The choice of field of view determines the expanse of the anatomical district analysed. VGi evo complies with international standards based on the "ALARA" (As Low As Reasonably Achievable) principle, whose purpose is to reduce the dose absorbed by the patient by selecting the most suitable FOV for the anatomical region of interest.

The exclusive Boosted and Enhanced modes allow to reach, when clinically required, excellent standards of image details and quality for exceptional uncompromising results.



HiRes



Choice of the best type of examination for specific diagnostic needs. The HiRes mode, which can be used for FOVs up to 15 x 5 cm, is ideal for localised anatomical regions with an amazing standard of detail and definition.

ECO

The ECO Scan mode, which can be used with all FOVs, allows to reduce the radiated dose by 50% to safeguard both patient and operator's health.

WIDE-RANGING FOVs



The most wide-ranging FOVs allow, with a single scan, to see complete images of the maxillofacial area for orthodontic applications, orthognathic and maxillofacial surgery.



24 x 19

MEDIUM-SIZE FOVs



Medium-size FOVs are indicated for ENT (otorhinolaryngology) and TMJ (Temporomandibular Joint) applications or full dentition examination and implant planning.



12 x 8

SMALL FOVs

Use of small FOVs is indicated for ENT, endodontic, periodontic and implantology examinations on specific user-selected regions.



5 x 5



CLINICAL APPLICATIONS.

VGI evo is a powerful and versatile device that expands the clinical use of CBCT.

Its wide range of examinations meets all needs of maxillofacial, otorhinolaryngology, dentistry and orthopaedic-cervical procedures.

The NNT software provides dedicated interfaces and tools to make the most of every specialist physician's work.

MAXILLO

FOVs up to 24 x 19 cm for a complete view of the entire maxillofacial area.

ENT

Very high definition examinations of the internal ear and complete airways.

DENTAL

Complete high quality dental applications for implantology, orthodontic treatment and endodontics.


CERVICAL REGION

Detailed analysis for morphological and functional assessments (CineX).

DENTAL CLINICAL APPLICATIONS.


ORAL AND MAXILLOFACIAL SURGERY

Highly precise details for oral and maxillofacial surgery applications, such as the presence of teeth or fractures, bone density and height, form and inclination of the root. The presence of metal elements does not impact image quality; instead, the small quantity of radiation reduces the scattering effect to a minimum and, therefore, anatomical structures are clearly displayed.





ORTHODONTICS

Cone Beam technology is ideally applied in orthodontic applications for aesthetic purposes and for the treatment of severe diseases. In fact, 3D images provide a very clear and detailed view of the investigated area, generating panoramic, teleradiographic and 3D images in which the area displayed can be modified and the thickness of reconstructed images can be adjusted.






IMPLANTOLOGY

Images produced by a 3D volume reveal diseases and structural anomalies, if any, with extreme detail. Cone Beam technology can generate detailed scans to effectively assess implant sites by obtaining in-depth information about the position, width, osseointegration process rate and any risk of rejection via a direct assessment of bone density at the site (Misch classification).



ENDODONTICS-PERIODONTICS





Clear and precise images with VGi evo for endodontic and periodontic applications, such as fractures, mandibular canal therapies and treatment of tissue adjacent to the tooth. These images help to identify every detail of the analysed area, determine the exact disease and correctly plan the most effective treatment.



SPECIALIST ANALYSES.






TMJ

High-quality 3D images in the anatomical representation of both the TMJ and the cervical region. Sagittal and coronal slices provide optimal imaging of the joint zone and are essential to identify any pathologies. Panoramic images provide important orthodontic information for initial screening, such as the difference between the height of the condyle and that of the mandibular ramus, or information on other dental pathologies.




EAR

With a single scan, VGi evo generates HiRes images of airways, both temporomandibular joints, maxillary and nasal sinuses. The clear and precise scans reveal a larger number of details of both the internal ear and the petrous bone. The ideal choice for otorhinolaryngology investigations.




UPPER AIRWAYS

Extra clear images, volume measurements and colour renderings that highlight the most critically narrow areas enable the assessment of airway disorders and diagnoses of sleep apnea (OSA) problems.



CERVICAL REGION

VGi evo allows detailed analyses of trabecular and cortical structures to identify any dysplastic, inflammatory, traumatic or micro-traumatic elements. Relationships between vertebral bodies are also perfectly legible, thus highlighting any distortion or subluxation. 3D volumes generated with VGi evo are ideal to examine the atlanto-occipital joint. Moreover, the dynamic CineX examination allows to study the moving site to ascertain the presence of any joint disorders.



VERSATILE 2D IMAGING.

Panoramic and cephalometric examinations for a precise and complete view.


The innovative VGi evo technology includes a low dose CBCT scan that has been specially developed for combined use with the patented Sharp 2D function, which generates a complete set of 2D images for diagnostic screening and post-surgery follow-up examinations.

Furthermore, the CineX mode offers the specialist physician a dynamic view of moving joints and internal structures.




Sharp 2D – TELERADIOGRAPHIC AND PANORAMIC SCANS

Exclusive function to create a dataset of images from Panoramic and Teleradiographic (AP, PA and LL) scans in a single examination. Compared to the panoramic scan-like coronal reconstructions (panorex) conventionally obtained with CBCT, images produced with Sharp 2D maintain the same magnification and orthogonality ratios; hence, the same clinical evaluation principles of conventional panoramic views apply. Latero-Lateral and Antero-Posterior teleradiographic scans can be used to perform cephalometric examinations and orthodontic rehabilitation.



CEPH MULTIPLE




DENT



PAN

CineX – DYNAMIC IMAGES

The innovative CineX function, which is provided with a 17 x 19 cm filming area, allows to investigate moving internal anatomical structures (e.g., swallowing, saliva ducts, TMJ disc, cervical vertebrae) by acquiring a sequence of X-rays in video format with AP, PA or LL projections. The videos obtained can then be directly consulted with the NNT software, with the NNT Viewer or exported and viewed with third party applications.



TMJ EXAMINATION



SWALLOWING ASSESSMENT

EXCEPTIONAL OPERATOR AND PATIENT COMFORT.

Functional features and design that facilitate relations and diagnosis.

VGi evo offers excellent ergonomics and stability during scans. The patented head support unit offers 7 contact points for rapid access and natural positioning of the patient.

Three laser lines precisely indicate the references of the area of interest. The mirror placed opposite the chin rest, and acquisition of two low dose scout (latero-lateral and antero-posterior) images provide a complete view of the patient, and allow to check correct position and perfect alignment.

VGi evo provides exclusive tools and technological solutions required to expose the patient only to the necessary dose by adapting to the clinical needs and anatomical characteristics of the area investigated.



USER-FRIENDLY CONTROL PANEL

The new control panel, with wide info display makes machine handling and patient positioning easier, allowing the operator to move the gantry and adjust its height to facilitate patient access to the scanning area. The patented head support unit can be adjusted in three directions and features positioning lasers, which can be activated with the dedicated button on the control panel.

EFFECTIVE COMMUNICATION

Precise diagnosis and complete planning of treatment ensure effective communications between specialist physician and patient, an essential requisite to learn about the treatment in a safe and trust-based setting.



ECO Scan

Pulsed emission technology activates the X-ray source only when necessary, thus limiting patient exposure to a minimum of 0.9 s with volume acquisition 5 x 5 cm and an effective minimum dose of 3.5 μ Sv.



aFOV

With the many dimensions that can be selected and the various scan modes available, examinations can be adapted to the specific requirements of a wide range of clinical applications.



SafeBeam™


SafeBeam™ technology automatically adapts emission according to the patient's anatomical characteristics, thus eliminating any risk of exposure to an unnecessarily high dose.

NNT. TECHNOLOGICAL HEART.

Technologically
advanced software
for 2D and
3D imaging.

With just a few simple steps NNT can process data acquired during the scan to create a vast array of images, which provide detailed information about patient anatomy.

They can subsequently be saved in a report or distributed with the Viewer version of the software. NNT also provides different application modes specifically intended for implantology, endodontics, periodontics, maxillofacial surgery and radiology.




NNT SOFTWARE COMPATIBILITY

NNT is DICOM 3.0 certified and can interface with third party systems and software to store and exchange medical data.


DENTISTRY: CROSS SECTIONS IN DENTAL PANORAMIC IMAGING

Complete view of the dental arches in cross sections to check shape, size and status of maxillary and mandibular bones and teeth.




OTORHINOLARYNGOLOGY: FREE MULTIPLANAR SECTIONS

Dynamic high resolution examination of the internal ear along non-orthogonal planes is essential to diagnose any diseases of the ossicular chain, stapes' base, semicircular canals, cochlea and adjacent structures.




GNATHOLOGY: DUAL TMJ VISION

Simultaneous view of both temporomandibular joints for symmetrical analysis and detection of problems or dysfunction deriving from joint diseases.



RADIOLOGY: MULTI-SLICE EXAMINATION

Creation of multiple image samples in Med-Like style with personalised orientation for the various assessments of anatomical areas, whose images have been acquired.



SPECIALIST TOOLS.

Dedicated tools to underpin diagnoses and treatment plan.



The software for NNT implant planning has advanced tools to measure the anatomic district (distances and angles) and trace the inferior alveolar nerve, making treatment planning safer and more precise.

CBCT scans can be processed and analysed to estimate bone density in potential implant sites.

IMPLANT SOFTWARE


The software for 3D implant planning. Designed to provide highly precise simulations of implant position, identify the mandibular canal, calculate bone density and define panoramic views and transversal section on bone models.

An essential technology that identifies the main anatomical aspects of the patient: implant position, any collision points and other clinical aspects. It is the ideal tool for rapid, efficient and safe design of prostheses and orthodontic implants.




IMPLANT SITE ASSESSMENT

Bone density estimate in a potential implant site, with Misch scale classification, to correctly plan treatment.




AIRWAY VOLUME ANALYSIS

Estimating the actual upper airway space is essential to diagnose respiratory diseases and sleep apnea (OSA).




2D AND 3D EVALUATION

The possibility to evaluate distances on 2D sections or with 3D rendering to verify any joint problems.



ADVANCED REPORTS

Advanced draft of medical reports to share on PACS, also available in automatic compiling mode.



COMPLETE CONNECTIVITY.

Excellent connectivity and integration with the modern systems adopted by NewTom. Workflow and clinical and diagnostic activities become much easier and highly performing.

REMOTE ASSISTANCE

By appropriately configuring the device to use the surgery's Internet connection, technical support can be provided from remote, and device status can be monitored.

3D/2D VIEWER

Examinations can be shared with colleagues and patients by providing the Viewer directly on CD, DVD or a USB storage device.

1:1 PRINT


Complete and flexible report for storing and sharing colour reports on photographic paper or grey scale reports on X-ray-equivalent transparencies.


OTHER ACQUISITION DEVICES

Compatibility with TWAIN standard and DICOM 3.0, guarantees the NNT software management of images from other 2D/3D image acquisition devices, such as video cameras, sensors, PSP and CBCT scanners.

MULTI-STATION DISPLAY AND PROCESSING

Image storage on a shared database in a local network that can be accessed from any workstation and iPad (only 2D). Management of multiple archives and access to password-protected data.





RIS/PACS

IHE compliant system that allows communication with RIS/PACS systems and DICOM printers. Complete services available: Print, Worklist, Storage Commitment, MPPS and Query/Retrieve.

SURGERY MANAGEMENT SOFTWARE

An open system designed for fast, efficient interfacing with the main dental surgery management software solutions via various standard VDDS, TWAIN and/or proprietary NNTBridge modes.

SPECIALIST PLANNING SOFTWARE

Exports in DICOM 3.0 format to specialist planning software to process orthodontic treatments, prostheses, implants, orthognatic and maxillofacial surgery.

3D MILLING PRINTERS


Software modules are available to segment the reconstructed volume and export to STL format the surfaces required to create 3D models that can underpin planning and treatment.

3D SCANNER


Prosthetically guided planning by integrating (via the dedicated software module) data in STL format from optical, intraoral or laboratory scanners, with volumetric data.

TECHNICAL SPECIFICATIONS.

| X-ray source | High frequency generator, rotating-anode X-ray tube; 75-110 kV, 1-32 mA (pulsed mode) | | | | | |
|------------------------------------|--|-------|--------------------------|---------|---------|----------|
| Focal spot | 0.3 mm | | | | | |
| Exposure Control | SafeBeam™ to reduce exposure according to patient build | | | | | |
| Sensor | Amorphous silicon flat panel | | | | | |
| Grey scale | 16-bit | | | | | |
| 3D scan time | 15 - 25s | | | | | |
| 3D emission time | 0.9s - 6s | | | | | |
| 3D image acquisition | Single scan with Cone Beam technology. 360° rotation | | | | | |
| Available FOV Diameter x Height | Resolution | | Selectable 3D scan modes | | | |
| | Standard | HiRes | Eco | Regular | Boosted | Enhanced |
| 24 x 19 cm | ■ | | ■ | ■ | ■ | ■ |
| 16 x 16 cm | ■ | | ■ | ■ | ■ | ■ |
| 15 x 12 cm | ■ | | ■ | ■ | ■ | ■ |
| 15 x 5 cm | ■ | ■ | ■ | ■ | ■ | ■ |
| 12 x 8 cm | ■ | ■ | ■ | ■ | ■ | ■ |
| 10 x 10 cm | ■ | ■ | ■ | ■ | ■ | ■ |
| 10 x 5 cm | ■ | ■ | ■ | ■ | ■ | ■ |
| 8 x 8 cm | ■ | ■ | ■ | ■ | ■ | ■ |
| 8 x 5 cm | ■ | ■ | ■ | ■ | ■ | ■ |
| 5 x 5 cm | ■ | ■ | ■ | ■ | ■ | ■ |
| Selectable voxel size Standard | 200 - 300 µm | | | | | |
| Selectable voxel size HiRes | 100 - 150 µm | | | | | |
| Reconstruction time | Less than 1 minute | | | | | |
| Image acquisition Sharp 2D | Panoramic and LL, AP and PA teleradiographic images from a single scan. Exposure 2.4s 75 kV | | | | | |
| CineX image acquisition | 1-36s Serial Radiography, field of view 17x19 cm (HxW) | | | | | |
| Patient positioning | Standing, sitting or in wheelchair | | | | | |
| Weight | Scan unit 377 kg, control box 95 kg | | | | | |
| Software | NewTom NNT with Viewer software, free | | | | | |
| DICOM nodes | IHE compliant (Print; Storage Commitment; WorkList MPPS; Query Retrieve) | | | | | |
| Power supply | 15A @ 100/115V~, 12.5A @ 200V~, 10A @ 220/230/240V~, 50/60Hz | | | | | |



Dimensions in centimetres
(dimensions in inches)



Cone Beam 3D Imaging
NewTom
what's next



CEFLA s.c.

Via Selice Provinciale 23/a • 40026 Imola • Italy
t. +39 045 8202727 • 045 583500
info@newtom.it

newtom.it